



仕様

1. 形式……
2. 電動機……全閉外扇カゴ形三相誘導電動機、
連続定格, 種絶縁, 200V 50/60Hz,
220V 60Hz. (0.1kWハ全閉カゴ形)
3. 減速比…… : 1
4. 寸法 "D" ……寸法公差ハJIS B0401-1976
"h6" デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……グリース潤滑

項	形式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低速軸端寸法					DM	J		L	重量(kg)	
		kW	rpm														D	b	h	t	ℓ		屋内形	屋外形		屋内形	屋外形
1	HM01-79	0.1	1500/ 1800	86	80	113	60	120	36	84	144	12	12	10	35	9	14	5	5	3	20	127	122	162	299	10	11
2	HM01-80	0.1		127	122	162	341	13	15																		
3	HM02-80	0.2		128	90	150	90	150	48	120	180	15	15	12	40	11	18	6	6	3.5	30	135	129	165	342	16	16
4	HM05-80	0.4		151	137	175	369	19	19																		
5	HM01-81	0.1		127	122	162	355	15	17																		
6	HM02-81	0.2		132	122	162	355	16	18																		
7	HM05-81	0.4		151	137	175	383	21	21																		
8	HM 1-81	0.75		173	143	165	389	23	23																		
9	HM02-82	0.2		132	122	162	369	18	20																		
10	HM05-82	0.4		151	137	175	397	23	23																		
11	HM 1-82	0.75		173	143	181	407	29	29																		
12	HM 2-82	1.5		176	137	177	421	29	31																		
13	HM05-83	0.4		151	125	165	410	31	33																		
14	HM 1-83	0.75		173	143	181	436	38	38																		
15	HM 2-83	1.5		202	156	195	478	48	50																		
16	HM 3-83	2.2		212	161	210	507	52	54																		
17	HM 5-83	3.7		215	160	195	514	55	57																		

御注文主	製番	承認	審査	設計	製図	尺度	品名	サイクロ減速機 外形図
						比例尺ニアラズ		
台数	項	三角法				昭和	年月日	
		住友重機械工業株式会社				図番	C 2001	G