



- 仕様
1. 形式……
  2. 電動機……全閉外扇カゴ形三相誘導電動機、連続定格、種絶縁、200V 50/60Hz、220V 60Hz.
  3. 減速比…… : 1
  4. 寸法 "D" …寸法公差ハJIS B0401-1976 "h6" デス。
  5. キー ……JIS B1301-1976 平行キー
  6. 潤滑方式……油浴式潤滑

項	形式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低速軸端寸法					S	ℓ <sub>2</sub>	DM	J		L	重量(kg)			
		kW	rpm														D	b	h	t	g				屋内形	屋外形		屋内形	屋外形		
																														屋内形	屋外形
1	HM 1-84	0.75	1500/1800	240	150	230	145	290	100	195	330	25	20	22	65	18	50	14	9	5.5	70	M10	18	173	143	165	492	54	56		
2	HM 2-84	1.5																							202	156		195	529	67	69
3	HM 3-84	2.2																							212	161		210	558	71	73
4	HM 5-84	3.7																							243	177		227	598	83	85
5	HM 8-84	5.5																							268	218		233	622	97	98
6	HM10-84	7.5																							258	197		233	660	106	110
7	HM 1-85	0.75		260	150	230	145	290	120	195	330	25	20	22	65	18	50	14	9	5.5	90	M10	18	151	125	165	512	55	57		
8	HM 2-85	1.5																							202	156		195	549	68	70
9	HM 3-85	2.2																							212	161		210	578	72	74
10	HM 5-85	3.7																							243	177		227	618	84	86
11	HM 3-86	2.2																							212	161		210	643	112	114
12	HM 5-86	3.7																							243	177		227	666	122	124
13	HM 8-86	5.5		308	160	320	150	370	139	238	410	44	20	25	75	18	60	18	11	7	90	M10	18	268	218	233	690	132	136		
14	HM10-86	7.5																							258	197		233	728	144	148
15	HM15-86	11																							324	232		268	794	176	180
16	HM20-86	15																							324	232		268	838	195	199

御注文主	製番	三角法	承認	審査	設計	製図	尺度	品名	サイクロ減速機 外形図
							比例尺ニアラズ		
台数	項	住友重機械工業株式会社				図番	C 2002		G