



仕様

1. 形式……
2. 電動機……全閉外扇カゴ形三相誘導電動機，
連続定格，種絶縁，200V 50/60Hz，
220V 60Hz.
3. 減速比…… : 1
4. 寸法 "D" …寸法公差ハJIS B0401-1976
"h6" デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……油浴式潤滑

項	形式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低速軸端寸法					S	ℓ ₂	DM	J		L	重量(kg)		
		kW	rpm														D	b	h	t	ℓ				屋内形	屋外形		屋内形	屋外形	
1	HM 5-87	3.7	1500 / 1800	352	200	340	275	380	125	335	430	30	25	30	64	22	70	20	12	7.5	90	M12	24	236	172	220	692	148	153	
2	HM 8-87	5.5																							218	233	734	168	172	
3	HM10-87	7.5																							258	197	233	772	181	184
4	HM15-87	11																							324	232	268	838	212	216
5	HM20-87	15																							324	232	268	882	231	235
6	HM30-87	22																							394	296	365	977	299	309
7	HM 5-88	3.7		389	220	370	320	420	145	380	470	30	25	30	73	22	80	22	14	9	110	M12	24	215	160	195	734	184	186	
8	HM 8-88	5.5																							258	197	233	769	203	207
9	HM10-88	7.5																							258	197	233	809	216	219
10	HM15-88	11																							324	232	268	875	247	251
11	HM20-88	15																							324	232	268	919	272	276
12	HM30-88	22																							394	296	365	1014	334	344
13	HM 8-89	5.5		465	250	430	380	480	170	440	530	30	25	35	90	26	95	25	14	9	135	M20	34	258	197	233	845	283	286	
14	HM10-89	7.5																							258	197	233	885	295	299
15	HM15-89	11																							324	232	268	951	326	330
16	HM20-89	15																							324	232	268	995	345	349
17	HM30-89	22																							394	296	365	1090	417	427
18	HM40-89	30																							394	296	365	1090	428	438

御注文主		製番		三角法	承認	審査	設計	製図	尺度	比例尺ニアラズ	品名	サイクロ減速機 外形図
台数	項			住友重機械工業株式会社					昭和	年 月 日	番 C 2003	G