



仕様

1. 形式……
2. 電動機……全閉外扇カゴ形三相誘導電動機,  
連続定格, 種絶縁, 200V 50/60Hz,  
220V 60Hz.
3. 減速比…… : 1
4. 寸法 "D" ……寸法公差ハJIS B0401-1976  
"h6" デス.
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……油浴式潤滑

項	形式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低速軸端寸法					S	ℓ <sub>2</sub>	DM	J		L	重量(kg)																									
		kW	rpm														D	b	h	t	ℓ				屋内形	屋外形		屋内形	屋外形																								
1	HM 15-90	11	1500 / 1800	570	290	505	240	560	215	560	620	40	30	40	100	26	110	28	16	10	170	M20	34	324	232	268	1056	466	470																								
2	HM 20-90	15																												324	232	268	1100	485	489																		
3	HM 30-90	22																																		394	296	365	1195	561	571												
4	HM 40-90	30																																								394	296	365	1195	573	583						
5	HM 50-90	37																																														394	296	365	1310	606	616
6	HM506-90	37																																																			
7	HM206-91	15	394	296	365	1286	702	712																																													
8	HM306-91	22							394	296	365	1286	722	732																																							
9	HM406-91	30													394	296	365	1401	767	777																																	
10	HM506-91	37																			394	296	365	1401	790	800																											
11	HM606-91	45																									485	415	487	1456	863	886																					
12	HM756-91	55																															485	415	487	1536	920	943															
			656	325	575	250	630	290																															600	690	50	30	40	105	26	120	32	18	11	210	M24	42	485

御注文主		製番		三角法	承認	審査	設計	製図	尺度	比例尺ニアラズ		品名	サイクロ減速機 外形図			
									昭和	年	月		日	図番	C	2004
台数		項		住友重機械工業株式会社				図番	C	2004						