



仕様

1. 形式……
2. 電動機……全閉外扇カゴ形三相誘導電動機,
連続定格, 種絶縁, 200V 50/60Hz,
220V 60Hz.
3. 減速比…… : 1
4. 寸法“D” …寸法公差ハJIS B0401-1976
“h6” デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式…… グリース潤滑

項	低速軸 定格 トルク kgf·m	形 式、	電 動 機		A	C	DC	E	F	G	M	N	P	Ø	R	V	d	低 速 軸 端 寸 法					S	ℓ ₂	DM	J		L	重 量 (kg)																																
			kW	rpm														D	b	h	t	ℓ				屋内形	屋外形		屋内形	屋外形																															
1	200	HM02-871B	0.2	1500 1800	418	200	340	275	380	125	335	430	30	25	30	64	22	70	20	12	7.5	90	M12	24	132	122	162	631	126	128																															
2		HM05-871B	0.4																												151	137	175	659	131	131																									
3		HM 1-871B	0.75																																		173	143	165	665	133	133																			
4	HM02-871A	0.2	474																												220	370	320	420	145	380							470	30	25	30	73	22	80	22	14	9	110	M12	24	132	122	162	631	126	128
5	HM05-871A	0.4																																			151	137	175	659	131	131																			
6	HM 1-871A	0.75																																																											
7	HM05-882B	0.4			176	137	177	739	175	177																																																			
8	HM 1-882B	0.75									173	143	181	725	175	175																																													
9	HM 2-882B	1.5			176	137	177	739	175	177																																																			
10	HM05-882A	0.4	151								137	175	715	169	169																																														
11	HM 1-882A	0.75			173	143	181	725	175	175																																																			
12	HM 2-882A	1.5	176								137	177	739	175	177																																														

御注文主	製番	三角法	承認	審査	設計	製図	尺度	比例尺ニアラズ		品名	サイクロ減速機 外形図
							昭和	年 月 日			
台数	項	住友重機械工業株式会社					図番	C	2008		G