



仕様

1. 形式……
2. 電動機……全閉外扇カゴ形三相誘導電動機、
連続定格、種絶縁、200V 50/60Hz、
220V 60Hz.
3. 減速比…… : 1
4. 寸法“D”…寸法公差ハJIS B0401-1976
“h6”デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……油浴式潤滑

項	低速軸 定格 トルク kgf·m	形 式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低 速 軸 端 寸 法					S	ℓ ₂	DM	J		L	重 量 (kg)	
			kW	rpm														D	b	h	t	ℓ				屋内形	屋外形		屋内形	屋外形
1	560	HM 1-893B	0.75	1500 1800	559	250	430	380	480	170	440	530	30	25	35	90	26	95	25	14	9	135	M20	34	173	143	181	806	260	260
2		HM 2-893B	1.5																						202	156	195	848	270	272
3		HM 3-893B	2.2																						212	161	210	877	274	276
4		HM 3-894B	2.2																						212	161	210	890	278	280
5		HM 5-894B	3.7																						243	177	227	930	290	292
6		HM 8-894B	5.5		268																				218	233	954	304	305	
7		HM10-894B	7.5		258																				197	233	992	313	317	
8		HM 5-896B	3.7		243																				177	227	959	314	316	
9		HM 8-896B	5.5		268																				218	233	983	324	328	
10		HM10-896B	7.5		258																				197	233	1021	336	340	
11	HM15-896B	11	324	232	268	1087	368	372																						
12	720	HM 1-893A	0.75	1500 1800	559	250	430	380	480	170	440	530	30	25	35	90	26	95	25	14	9	135	M20	34	173	143	181	806	260	260
13		HM 2-893A	1.5																						202	156	195	848	270	272
14		HM 3-893A	2.2																						212	161	210	877	274	276
15		HM 5-894A	3.7		243																				177	227	930	290	292	
16		HM 5-896A	3.7		243																				177	227	959	314	316	
17		HM 8-896A	5.5		268																				218	233	983	324	328	
18		HM10-896A	7.5		258																				197	233	1021	336	340	
19		HM15-896A	11		324																				232	268	1087	368	372	

御注文主	製番	承認	審査	設計	製図	尺 度	品 名	サイクロ減速機 外形図
						比例尺ニアラズ		
台 数	項	住友重機械工業株式会社				図 番	C 2010	G