



- 仕様
1. 形式……
 2. 電動機……全閉外扇カゴ形三相誘導電動機、
(0.1~0.4kWハ全閉カゴ形)、連続定格、
種絶縁 200V 50/60Hz. 220V 60Hz.
(CMBブレーキ付、屋外形ハ屋外カバー付)
 3. 減速比…… : 1
 4. 寸法 "D" ……寸法公差ハJIS B0401-1976
"h6" デス。
 5. キー ……JIS B1301-1976 平行キー
 6. 潤滑方式……グリース潤滑

項	形式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低速軸端寸法					DM	J		T	r	L	重量(kg)	
		kW	rpm														D	b	h	t	ℓ		屋外形	屋外形				屋外形	屋外形
1	HM01-79	0.1	1500/ 1800	86	80	113	60	120	36	84	144	12	12	10	35	9	14	5	5	3	20	126	122	162	/	/	345	12	14
2	HM01-80	0.1		126	122	162	/	/	387	16	18																		
3	HM02-80	0.2		128	90	150	90	150	48	120	180	15	15	12	40	11	18	6	6	3.5	30	126	122	162	/	/	387	17	19
4	HM05-80	0.4		176	136	176	/	/	448	28	30																		
5	HM01-81	0.1		126	122	162	/	/	401	18	35																		
6	HM02-81	0.2		126	122	162	/	/	401	19	35																		
7	HM05-81	0.4		176	137	176	10	95	464	30	35																		
8	HM 1-81	0.75		180	151	176	30	98	452	33	35																		
9	HM02-82	0.2		126	122	162	/	/	415	21	35																		
10	HM05-82	0.4		176	137	176	10	95	478	32	35																		
11	HM 1-82	0.75		180	151	176	30	98	487	35	35																		
12	HM 2-82	1.5		180	151	176	30	98	511	40	35																		
13	HM05-83	0.4		176	137	176	10	95	509	43	35																		
14	HM 1-83	0.75		180	151	176	30	98	505	46	35																		
15	HM 2-83	1.5		202	156	176	30	98	568	51	35																		
16	HM 3-83	2.2		230	177	202	30	125	574	69	35																		
17	HM 5-83	3.7		230	177	202	30	125	614	78	35																		

御注文主		製番		承認		審査		設計		製図		尺度		比例尺ニアラズ		品名	サイクロ減速機 外形図
台数	項	住友重機械工業株式会社								図番	C	2053					G