



仕様

1. 形式……HM
2. 電動機……全閉外扇カゴ形三相誘導電動機、
連続定格、種絶縁、200V 50/60Hz、
220V 60Hz. CMBブレーキ付、屋外形ハ屋
外カバー付)
3. 減速比…… : 1
4. 寸法“D” ……寸法公差ハJIS B0401-1976
“h6” デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……油浴式潤滑

項	形式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低速軸端寸法						DM	J		T	r	L	重量(kg)										
		kW	rpm														D	b	h	t	ℓ	S		ℓ ₂	屋内形				屋外形	屋内形	屋外形								
1	HM 1-84	0.75	1500/ 1800	240	150	230	145	290	100	195	330	25	20	22	65	18	50	14	9	5.5	70	M10	18	180	151	176	30	98	550	65	68								
2	HM 2-84	1.5																														202	156	176	30	98	619	70	74
3	HM 3-84	2.2																														230	177	202	30	125	625	88	93
4	HM 5-84	3.7																														230	177	202	30	125	665	97	102
5	HM 8-84	5.5																														260	197	233	30	140	725	120	126
6	HM10-84	7.5																														260	197	233	30	140	765	134	141
7	HM 1-85	0.75		260	150	230	145	290	120	195	330	25	20	22	65	18	50	14	9	5.5	90	M10	18	180	151	176	30	98	570	66	69								
8	HM 2-85	1.5																														202	156	176	30	98	639	71	75
9	HM 3-85	2.2																														230	177	202	30	125	645	89	94
10	HM 5-85	3.7																														230	177	202	30	125	685	98	103
11	HM 3-86	2.2																														230	177	202	30	125	693	125	130
12	HM 5-86	3.7																														230	177	202	30	125	733	135	140
13	HM 8-86	5.5		308	160	320	150	370	139	238	410	44	20	25	75	18	60	18	11	7	90	M10	18	260	197	233	30	140	793	159	165								
14	HM10-86	7.5																														260	197	233	30	140	833	173	180
15	HM15-86	11																														321	232	268	30	167	884	210	220
16	HM20-86	15																														321	232	268	30	167	928	228	238

御注文主		製番		承認		審査		設計		製図		尺度		品名	
													比例尺ニアラズ		サイクロ減速機 外形図
													昭和 年 月 日		
台数	項			住友重機械工業株式会社								図番	C 2054		G