



仕様

1. 形式……
2. 電動機……全閉外扇カゴ形三相誘導電動機,
(0.2~0.4kWハ全閉カゴ形) 種絶縁,
連続定格, 200V 50/60Hz. 220V 60Hz
(CMBブレーキ付, 屋外形ハ屋外カバー付)
3. 減速比…… : 1
4. 寸法 "D" …寸法公差ハJIS B0401-1976
"h6" デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……グリース潤滑

項	低速軸 定格 トルク kgf·m	形 式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低速軸端寸法								DM	J		T	r	L	重量(kg)																											
			kW	rpm														D	b	h	t	ℓ	S	ℓ ₂	屋外形		屋外形	屋外形				屋外形																											
																																	屋外形	屋外形	屋外形	屋外形																							
1	200	HM02-871B	0.2	1500/ 1800	418	200	340	275	380	125	335	430	30	25	30	64	22	70	20	12	7.5	90	M12	24	126	122	162	10	95	677	129	131																											
2		HM05-871B	0.4																						176	137	176						140	144																									
3		HM 1-871B	0.75																						180	151	176								143	146																							
4	HM02-871A	0.2	126																						122	162	677										129	131																					
5	HM05-871A	0.4	176																						137	176													740	140	144																		
6	HM 1-871A	0.75	180																						151	176																728	143	146															
7	HM05-882B	0.4	176																						137	176																			796	178	182												
8	HM 1-882B	0.75	180																						151	176																						805	181	184									
9	HM 2-882B	1.5	180																						151	176																									829	186	190						
10	HM05-882A	0.4	176																						136	176																												784	178	182			
11	HM 1-882A	0.75	180																						151	176																															805	181	184
12	HM 2-882A	1.5	180																						151	176																																	

御注文主	製 番	三角法	承認	審査	設計	製図	尺 度	比例尺ニアラズ	品 名	サイクロ減速機 外形図
			昭和	年	月	日	番			
台 数	項	住友重機械工業株式会社					図 番	C	2059	G