



仕様

1. 形式……HM
2. 電動機……全閉外扇カゴ形三相誘導電動機、
連続定格、種絶縁、200V 50/60Hz、
220V 60Hz。(CMBブレーキ付、屋外形ハ屋
外カバー付)
3. 減速比…… : 1
4. 寸法“D”…寸法公差ハJIS B0401-1976
“h6”デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……油浴式潤滑

項	低速軸 定格 トルク kgf·m	形 式	電動機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低速軸端寸法								DM	J		T	r	L	重量(kg)	
			kW	rpm														D	b	h	t	l	s	l ₂	屋外形		屋外形	屋外形				屋外形	
																																	屋外形
1	560	HM 1-893B	0.75	1500/ 1800	559	250	430	380	480	170	440	530	30	25	35	90	26	95	25	14	9	135	M20	34	180	151	176	30	98	875	268	271	
2		HM 2-893B	1.5																							202	156	176	30	98	938	273	277
3		HM 3-893B	2.2																							230	177	202	30	125	944	291	296
4		HM 3-894B	2.2																							230	177	202	30	125	957	295	300
5		HM 5-894B	3.7																							230	177	202	30	125	997	304	309
6		HM 8-894B	5.5		260																					197	233	30	140	1057	327	333	
7		HM10-894B	7.5		260																					197	233	30	140	1097	341	348	
8		HM 5-896B	3.7		230																					177	202	30	125	1026	327	332	
9		HM 8-896B	5.5		260																					197	233	30	140	1086	351	357	
10		HM10-896B	7.5		260																					197	233	30	140	1126	365	372	
11		HM15-896B	11		321																					232	268	30	167	1177	402	412	
12	720	HM 1-893A	0.75	1500/ 1800	559	250	430	380	480	170	440	530	30	25	35	90	26	95	25	14	9	135	M20	34	180	151	176	30	98	875	268	271	
13		HM 2-893A	1.5																							202	156	176	30	98	938	273	277
14		HM 3-893A	2.2																							230	177	202	30	125	944	291	296
15		HM 5-894A	3.7																							230	177	202	30	125	997	304	309
16		HM 5-896A	3.7																							230	177	202	30	125	1026	327	332
17		HM 8-896A	5.5		260																					197	233	30	140	1086	351	357	
18		HM10-896A	7.5		260																					197	233	30	145	1126	365	372	
19		HM15-896A	11		321																					232	268	30	167	1177	402	412	

御注文主	製 番	三角法	承認	審査	設計	製図	尺度	比例尺ニアラズ		品 名	サイクロ減速機 外形図	
							昭和	年月日				
台数	項	住友重機械工業株式会社					図番	C	2061		G	