



仕様

1. 形式……HM
2. 電動機……全閉外扇カゴ形三相誘導電動機、
連続定格、種絶縁、200V 50/60Hz、
220V 60Hz。(CMBブレーキ付、屋外形ハ屋
外カバー付)

3. 減速比…… : 1
4. 寸法“D” ……寸法公差ハJIS B0401-1976
“h6” デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……油浴式潤滑

項	低速軸 定格 トルク kgf·m	形 式	電 動 機		A	C	DC	E	F	G	M	N	P	Q	R	V	d	低 速 軸 端 寸 法						DM	J		T	r	L	重 量(kg)			
			kW	rpm														D	b	h	t	ℓ	S		ℓ ₂	屋内形				屋外形	屋内形	屋外形	
1	720	HM15-906A	11	1500/ 1800	705																		321	232	268	30	167	1281	548	558			
2		HM 2-904B	1.5																					202	156	176	30	98	1060	420	424		
3		HM 3-904B	2.2																					230	177	202	30	125	1066	438	443		
4		HM 5-904B	3.7			681																		230	177	202	30	125	1106	447	452		
5	1000	HM 8-904B	5.5				290	505	240	560	215	560	620	40	30	40	100	26	110	28	16	10	170	M20	34	260	197	233	30	140	1166	470	476
6		HM 8-906B	5.5																					260	197	233	30	140	1190	497	503		
7		HM10-906B	7.5			705																		260	197	233	30	140	1230	511	518		
8		HM15-906B	11																					321	232	268	30	167	1281	548	558		
9		HM20-917B	15			811	325	575	250	630	290	600	690	50	30	40	105	26	120	32	18	11	210	M24	42	321	232	268	30	167	1431	731	741
10		HM 2-904A	1.5																					202	156	176	30	98	1060	420	424		
11		HM 3-904A	2.2																					230	177	202	30	125	1066	438	443		
12		HM 5-904A	3.7			681	290	505	240	560	215	560	620	40	30	40	100	26	110	28	16	10	170	M20	34	230	177	202	30	125	1106	447	452
13		HM 8-904A	5.5																					260	197	233	30	140	1166	470	476		
14		HM 3-916B	2.2																					230	177	202	30	125	1189	604	609		
15		HM 5-916B	3.7																					230	177	202	30	125	1229	614	619		
16		HM 8-916B	5.5			804																		260	197	233	30	140	1289	638	644		
17	1500	HM10-916B	7.5																					260	197	233	30	140	1329	652	659		
18		HM10-917B	7.5																					260	197	233	30	140	1336	675	682		
19		HM15-917B	11			811	325	575	250	630	290	600	690	50	30	40	105	26	120	32	18	11	210	M24	42	321	232	268	30	167	1387	713	723
20		HM20-917B	15																					321	232	268	30	167	1431	731	741		
21		HM 3-916A	2.2																					230	177	202	30	125	1189	604	609		
22	1800	HM 5-916A	3.7																					230	177	202	30	125	1229	614	619		
23		HM 8-916A	5.5			804																		260	197	233	30	140	1289	638	644		
24		HM10-916A	7.5																					260	197	233	30	140	1329	652	659		

御注文主	製 番		三角法	承認	審査	設計	製図	尺度	比例尺ニアラズ		品名	サイクロ減速機 外形図			
	台数			昭和	年	月	日	昭	和	年		月	日	図番	C