



仕様

1. 形式……HM
2. 電動機……全閉外扇カゴ形三相誘導電動機、
連続定格, 種絶縁, 200V 50/60Hz,
220V 60Hz.
3. 減速比…… : 1
4. 寸法 "D" 及ビ "D₃" ……寸法公差ハJIS
B0401-1976 "h6" 及ビ "f8" デス。
5. キー ……JIS B1301-1976 平行キー
6. 潤滑方式……強制油潤滑
(減速比ニ依ッテハグリース潤滑トナリマス)

項	低速軸 定格トルク kgf·m	形 式	電動機		CF	D ₁	D ₂	D ₃	E	M	N	P	d	低速軸端寸法						DM	J		L	重 量 (kg)																		
			kW	rpm										D	b	h	t	ℓ	S		ℓ ₂	屋外形		屋外形	屋外形	屋外形																
																											屋内形	屋内形	屋内形	屋内形												
1	200	VM1-873B	0.75	1500/1800	345	400	360	316	22	94	8	5	14	70	20	12	7.5	84	M12	24	173	143	181	686	148	148																
2		VM2-873B	1.5																		202	156	195	728	158	160																
3		VM3-873B	2.2																		212	161	210	757	162	164																
4		VM5-873B	3.7																		215	160	195	764	165	167																
5	VM2-873A	1.5	202																		156	195	728	158	160																	
6	VM3-873A	2.2	212																		161	210	757	162	164																	
7	VM5-873A	3.7	215																		160	195	764	165	167																	
8	300	VM3-884B	2.2		386	430	390	345	22	110	8	5	18	80	22	14	9	100	M12	24	212	161	210	814	196	198																
9		VM5-884B	3.7																		243	177	227	854	208	210																
10		VM8-884B	5.5																		268	218	233	878	222	223																
11	360	VM2-884A	1.5																		386	430	390	345	22	110	8	5	18	80	22	14	9	100	M12	24	202	156	195	785	192	194
12		VM3-884A	2.2																																		212	161	210	814	196	198
13		VM5-884A	3.7																																		243	177	227	854	208	210
14		VM8-884A	5.5																																		268	218	233	878	222	223

御注文主		製番		承認	審査	設計	製図	尺 度	比例尺ニアラズ	品 名	サイクロ減速機 外形図
台数	項		住友重機械工業株式会社	図番	C	2025					G