

モータ製作範囲一覧表

表 3 非防爆形三相誘導モータ（屋内形・屋外形）

モータ種類	三相モータ	プレミアム効率 三相モータ	インバータ用 AF モータ	インバータ用 プレミアム効率 三相モータ	高効率三相モータ
kW	4P	4P	4P	4P	4P
0.1	●		●		
0.2	●		●		●
0.25	●				
0.4	●		●		●
0.55	●				
0.75		●		●	
1.1		●			
1.5		●		●	
2.2		●		●	
3.0		●			
3.7		●		●	
5.5		●		●	
7.5		●		●	
11		●		●	
15		●		●	
18.5		●		●	
22		●		●	
30		●			
仕様	時間定格：S1（連続） 電源：200V 50/60Hz、220V 60Hz または 400V 50/60Hz、440V 60Hz ただしインバータ用は 200V 60Hz、220V 60Hz または 400V 60Hz、440V 60Hz				

表 4 非防爆形三相誘導モータ 内蔵ブレーキ付（屋内形・屋外形）

モータ種類	三相モータ	プレミアム効率 三相モータ	インバータ用 AF モータ	インバータ用 プレミアム効率 三相モータ	高効率三相モータ
kW	4P	4P	4P	4P	4P
0.1	●		●		
0.2	●		●		●
0.25	●				
0.4	●		●		●
0.55	●				
0.75		●		●	
1.1		●			
1.5		●		●	
2.2		●		●	
3.0		●			
3.7		●		●	
5.5		●		●	
7.5		●		●	
11		●		●	
15		●		●	
18.5		●		●	
22		●		●	
30		●			
仕様	時間定格：S1（連続） 電源：200V 50/60Hz、220V 60Hz または 400V 50/60Hz、440V 60Hz ただしインバータ用は 200V 60Hz、220V 60Hz または 400V 60Hz、440V 60Hz				

- 注) 1. 上記の電圧以外も製作可能です。
 2. 使用環境オプションモータ（IP55 屋外形・防塵形・防爆形・防食形・防水形・海外仕様など）については、ご照会ください。
 3. ブレーキ形式は技術資料をご参照ください。

Basic Motor Specifications

Table 3. 3-Phase Induction Motors (Indoor type & Outdoor type)

Motor Type	3-Phase Motor	Premium Efficiency (IE3) 3-Phase Motor	3-Phase Inverter Duty Motor	Premium Efficiency (IE3) 3-Phase Inverter Duty Motor	High Efficiency (JIS) 3-Phase Motor
kW	4P	4P	4P	4P	4P
0.1	●		●		
0.2	●		●		●
0.25	●				
0.4	●		●		●
0.55	●				
0.75		●		●	
1.1		●			
1.5		●		●	
2.2		●		●	
3.0		●			
3.7		●		●	
5.5		●		●	
7.5		●		●	
11		●		●	
15		●		●	
18.5		●		●	
22		●		●	
30		●			
仕様	Time Rating : S1(Continuous) Applicable Voltage : [200V 50/60Hz, 220V 60Hz] or [400V 50/60Hz, 440V/60Hz] (For Inverter Drive) : [200V 60Hz, 220 V 60Hz] or [400V 60Hz, 440V 60Hz]				

Table 4. 3-Phase Induction Motors with brake (Indoor type & Outdoor type)

Motor Type	3-Phase Motor	Premium Efficiency (IE3) 3-Phase Motor	3-Phase Inverter Duty Motor	Premium Efficiency (IE3) 3-Phase Inverter Duty Motor	High Efficiency (JIS) 3-Phase Motor
kW	4P	4P	4P	4P	4P
0.1	●		●		
0.2	●		●		●
0.25	●				
0.4	●		●		●
0.55	●				
0.75		●		●	
1.1		●			
1.5		●		●	
2.2		●		●	
3.0		●			
3.7		●		●	
5.5		●		●	
7.5		●		●	
11		●		●	
15		●		●	
18.5		●		●	
22		●		●	
30		●			
仕様	Time Rating : S1(Continuous) Applicable Voltage : [200V 50/60Hz, 220V 60Hz] or [400V 50/60Hz, 440V/60Hz] (For Inverter Drive) : [200V 60Hz, 220 V 60Hz] or [400V 60Hz, 440V 60Hz]				

注) 1. Motors with other voltage than as listed are manufactured. Consult us.

2. Consult us about environmental options, for example outdoor type (IP55), special Voltage, dust-proof, explosion-proof, corrosion-proof, water-proof, overseas standard and so on.

3. Refer technical data for specification of brake.